

COMMERCIAL COVERS

LOOP-LOC Keeps Your Facility Safe and Saves You Money.

In the off season, an empty, unsupervised commercial pool can be an invitation for disaster. Locked gates or fences alone have often proved ineffective in preventing children and pets from gaining access to the pool area.

2000
POUND
MINIMAL BREAK
STRENGTH

**BUILT
SUPER
STRONG**
TO PROTECT
CHILDREN

15
YEAR
PRORATED
WARRANTY



- ✓ Save big on water because the pool doesn't need to be drained at the end of every season.
- ✓ Extend the life of your pool by reducing the need for repainting or replastering.
- ✓ Have the potential to lower your liability insurance premium.
- ✓ Help the environment. Keeping the pool filled means you don't have to worry about disposing of chlorine and chemically treated water, an environmental hazard that many states are in the process of regulating.



Manual Safety Cover
In accordance with ASTM
Standard F 1346-91

MINIMUM SPECIFICATIONS

For Commercial Installations To Meet ASTM Standard F1346-91

MATERIAL: Polypropylene-extruded monofilament yarn. 525 denier in the warp and 595 denier in fill. 41 x 20 construction plus 80% minimum black yarn and 20% minimum green yarn for best U.V. stability. Burst strength of material is 650 P.S.I.

WEBBING: 1" wide polypropylene, polyester with nylon filler. Minimum break strength 2,000 pounds single. To be used double-thick for minimum strap break-strength of 4,200 pounds. Minimum 90% black yarn. (Cotton, wool or other natural fibers treated or untreated are unacceptable for safety cover use).

CHAFING STRIPS: (Under cover) 1" minimum width, 20" to 36" long (depending on cover overlap) extruded solid, virgin vinyl 3/16" thick. All inside corners heavily padded.

SAFETY BARRIER/GAPGUARD®: Solid, virgin vinyl 3" extrusion for raised walls, etc., and 15" extrusion for raised steps as needed to meet (or exceed) ASTM Safety Standard F1346-91. LOOP-LOC Patent No. 4,982,457.

THREAD: Dabond polyester Veemo - UVR. Size 138. Three rows of stitching all directions.

SPRINGS: 302/304 stainless steel, two draw-bar compression type with thick vinyl tubular deck-protective covers. Break strength 3,200 pounds.

ANCHORS: Brass, flush-mounted in deck with screw-type insert. 4,000 pound break strength at neck.

INSTALLATION TOOLS: 30" long steel rod, with notched end and plastic grip.

FINISHED COVER: To have sections approximately 3' x 3'. (For residential rectangular pools only, cover may be made with approximately 5' x 5' sections.) All straps to be "X"-tacked at cover edge with stainless steel buckles and aluminum tips.

WARRANTY: Safety cover will have a 15 year prorated warranty.